

LED Test Report

Product Mark

Product Type :SP-PZT-R110-3P-RDM

Manufacturer :TPK


Temperature :22.5'C

Humidity :42%

Operator :qc1

Test Date :2025-07-31 16:56:28

Remark:8.03.036.0003 45° SP-PZT-R110-3P-RDM

**Chroma Parameters**

Chro.Coar.:x=0.2889 y=0.2605 u=0.2083 v=0.2817 duv=-0.0212

CCT:10967K Dominant Wave.:458.4nm Purity:23.8%

Flux RGB Ratio:R=24.8%,G=65.3%,B=9.9% Peak Wave:466.7nm Half Width:25.7nm

Rendering Index:Ra= 36.0

R1 =14 R2 =43 R3 =77 R4 =34 R5 =31 R6 =40 R7 =60 R8 =-10

R9 =-217 R10=-24 R11=23 R12=33 R13=18 R14=84 R15=-4

Photo Parameters

Flux:602.44lm

Effi.:33.5lm/W

Radiant:2626.8mW

Iv:0.0mcd

Efficiency:0.352

Effi Level:B (EU 874-2012)

Ele. Parameters

Voltage:U=120.500V

Current:I=0.2550A

Power:P=18.00W

Power Factor:PF=0.584

Instrument state

Instrument:Hopoo HP8000S

Integral Time: 77.681ms

VPeak: 14825

VDark: 1241

Scan Range: 380-780nm

Product ID: 201605038